Version 4.7

Revision Date 26.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: AeroShell Fluid 31
Product code	: 001A0048
UFI	: QVP0-D0PQ-Y001-RN70

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Synthetic hydrocarbon hydraulic fluid for aircraft., For further details consult the AeroShell Book on www.shell.com/aviation.
Uses advised against		This product must be used, handled and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation. This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Shell UK Oil Products Limited Shell Centre London SE1 7NA United Kingdom
Telephone	: (+44) 08007318888
Telefax	
Email Contact for Safety Data Sheet	: If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com
1.4 Emergency telephone num	ber

: +44 (0) 151 350 4595 (This telephone number is available 24 hours per day, 7 days per week)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters
Long-term (chronic) aquatic hazard, Category 3	airways. H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

AeroShell Fluid 31

Version 4.7	Revision Date	26.03.2021	Print Date 27.03.2021
Hazard pictograms			
Signal word	: Danger		
Hazard statements	: H304	PHYSICAL HAZARDS Not classified as a physic according to CLP criter HEALTH HAZARDS: May be fatal if swallow	sical hazard ia.
	11304	airways. ENVIRONMENTAL HA	
	H412	Harmful to aquatic life effects.	with long lasting
Precautionary statements	: Prevention:		
	P273 Response:	Avoid release to the en	vironment.
	P331 P301 + P310	Do NOT induce vomitir IF SWALLOWED: Imm POISON CENTER/ do	ediately call a
	Storage: P405 Disposal:	Store locked up.	
	P501	Dispose of contents/ co approved waste dispos	

Hazardous components which must be listed on the label: Contains low viscosity polyalphaolefins.

Sensitising components

Contains triazole derivatives. May produce an allergic reaction.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Blend of polyolefins, synthetic esters and additives.

Version 4.7

Revision Date 26.03.2021

Print Date 27.03.2021

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Polyolefin	68037-01-4	Asp. Tox.1; H304	60 - 80
Alkylphenol	118-82-1 204-279-1	Aquatic Chronic4; H413	1 - 3
Phenol, isobutylenated, phosphate (3:1)	68937-40-6 273-065-8 01-2119519251-50	Aquatic Acute1; H400 Aquatic Chronic1; H410	0.5 - 1
Triazole derivative	91273-04-0 401-280-0	Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Chronic1; H410	0.01 - 0.099

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
		When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.

AeroShell Fluid 31 Version 4.7 Revision Date 26.03.2021 Print Date 27.03.2021 If swallowed : Call emergency number for your location / facility. If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : If material enters lungs, signs and symptoms may include

a material enters largs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
 The onset of respiratory symptoms may be delayed for several hours after exposure.
 Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.
 Ingestion may result in nausea, vomiting and/or diarrhoea.

Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: Potential for chemical pneumonitis. Call a doctor or poison control center for guidance.
	High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.
5.2 Special hazards arising from	the substance or mixture
Specific hazards during	: Hazardous combustion products may include: A complex

AeroShell Fluid 31

Version 4.7	Revision Date 26.03.2021	Print Date 27.03.2021
firefighting	mixture of airborne solid and liquid particu (smoke). Carbon monoxide may be evolv combustion occurs. Unidentified organic a compounds.	ed if incomplete
5.3 Advice for firefighters		
Special protective equipment for firefighters	: Proper protective equipment including che gloves are to be worn; chemical resistant large contact with spilled product is expec Breathing Apparatus must be worn when a confined space. Select fire fighter's clott relevant Standards (e.g. Europe: EN469)	suit is indicated if cted. Self-Contained approaching a fire in hing approved to
Specific extinguishing methods	: Use extinguishing measures that are app circumstances and the surrounding enviro	ropriate to local

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: 6.1.1 For non emergency personnel:
	Avoid contact with skin and eyes.
	6.1.2 For emergency responders:
	Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions	: Use appropriate containment to avoid environmental
	contamination. Prevent from spreading or entering drains,
	ditches or rivers by using sand, earth, or other appropriate
	barriers.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	 Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material.
	Reclaim liquid directly or in an absorbent.
	Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

General Precautions : Use local exhaust ventilation if there is risk of inhalation of

AeroShell Fluid 31		
Version 4.7	Revision Date 26.03.2021	Print Date 27.03.2021
	vapours, mists or aerosols. Use the information in this data shee assessment of local circumstances to appropriate controls for safe handling this material.	o help determine
7.1 Precautions for safe handling	g	
Advice on safe handling	: Avoid prolonged or repeated contact Avoid inhaling vapour and/or mists. When handling product in drums, saf worn and proper handling equipment Properly dispose of any contaminate materials in order to prevent fires.	fety footwear should be t should be used.
7.2 Conditions for safe storage,	including any incompatibilities	
Other data	: Keep container tightly closed and in a place. Use properly labeled and clos	
	Store at ambient temperature.	
	Refer to section 15 for any additional covering the packaging and storage	
	The storage of this product may be s Pollution (Oil Storage) (England) Reg guidance may be obtained from the I agency office.	gulations. Further
Packaging material	: Suitable material: For containers or c steel or high density polyethylene. Unsuitable material: PVC.	container linings, use mild
Container Advice	: Polyethylene containers should not b temperatures because of possible ris	
7.3 Specific end use(s)		
Specific use(s)	: Not applicable.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Biological occupational exposure limits

No biological limit allocated. **Monitoring Methods**

AeroShell Fluid 31

Version 4.7

Print Date 27.03.2021

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Revision Date 26.03.2021

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

8.2 Exposure controls

Engineering measures The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Do not ingest. If swallowed, then seek immediate medical assistance

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

AeroShell Fluid 31

sion 4.7	Revision Date 26.03.2021	Print Date 27.03.202
Eye protection	: If material is handled such that it couprotective eyewear is recommended Approved to EU Standard EN166.	
Hand protection		
Remarks	: Where hand contact with the product gloves approved to relevant standar US: F739) made from the following r suitable chemical protection. PVC, n gloves Suitability and durability of a usage, e.g. frequency and duration of resistance of glove material, dexterit from glove suppliers. Contaminated replaced. Personal hygiene is a key care. Gloves must only be worn on of gloves, hands should be washed an Application of a non-perfumed moist	ds (e.g. Europe: EN374, materials may provide neoprene or nitrile rubber glove is dependent on of contact, chemical ty. Always seek advice gloves should be element of effective hand clean hands. After using d dried thoroughly.
	For continuous contact we recomme breakthrough time of more than 240 for > 480 minutes where suitable glo short-term/splash protection we reco recognize that suitable gloves offerir may not be available and in this case time maybe acceptable so long as a and replacement regimes are follow a good predictor of glove resistance dependent on the exact composition Glove thickness should be typically g depending on the glove make and m	minutes with preference oves can be identified. For ommend the same but ng this level of protection e a lower breakthrough ppropriate maintenance ed. Glove thickness is not to a chemical as it is of the glove material. greater than 0.35 mm
Skin and body protection	: Skin protection is not ordinarily requ work clothes. It is good practice to wear chemical	
Respiratory protection	 No respiratory protection is ordinarily conditions of use. In accordance with good industrial h precautions should be taken to avoid If engineering controls do not mainta concentrations to a level which is ad health, select respiratory protection of specific conditions of use and meetin Check with respiratory protective eq Where air-filtering respirators are su appropriate combination of mask an Select a filter suitable for combined and vapours [Type A/Type P boiling meeting EN14387 and EN143. 	ygiene practices, d breathing of material. ain airborne lequate to protect worker equipment suitable for the ng relevant legislation. uipment suppliers. itable, select an d filter. particulate/organic gases

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Fluid 31	o as amenued as at the date of this SDS	
ersion 4.7	Revision Date 26.03.2021	Print Date 27.03.202
Thermal hazards	: Not applicable	
Hygiene measures	: Exposure to this product should be reasonably practicable. Reference shealth and Safety Executive's public Essentials".	hould be made to the
Environmental exposu	e controls	
General advice	 Local guidelines on emission limits for must be observed for the discharge of vapour. Minimise release to the environment assessment must be made to ensure environmental legislation. Information on accidental release me section 6. Take appropriate measures to fulfil the relevant environmental protection legis contamination of the environment by Section 6. If necessary, prevent und being discharged to waste water. Wate treated in a municipal or industrial wate before discharge to surface water. 	of exhaust air containing A An environmental compliance with local easures are to be found in the requirements of gislation. Avoid of following advice given in dissolved material from aste water should be

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	Liquid at room temperature.
Colour	:	red
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	<= -55 °CMethod: ASTM D97
Melting / freezing point		Data not available
Initial boiling point and boiling range	:	> 280 °Cestimated value(s)
Flash point	:	>= 205 °C Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available

AeroShell Fluid 31

Version 4.7	Revision Date 26.03.2021	Print Date 27.03.2021
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Relative density	: 0.850 (15 °C)	
Density	: 850 kg/m3 (15.0 °C) Method: Unspecified	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6(based on information c	on similar products)
Auto-ignition temperature	: > 320 °C	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 1.06 mm2/s (205 °C) Method: ASTM D445	
	3.53 mm2/s (100 °C) Method: ASTM D445	
	14.3 mm2/s (40.0 °C) Method: ASTM D445	
	2059 mm2/s (-40 °C) Method: ASTM D445	
Explosive properties	: Not classified	
Oxidizing properties	: Data not available	

9.2 Other information

AeroShell Fluid 31

Version 4.7	Revision Date 26.03.2021	Print Date 27.03.2021

Conductivity : This material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with strong oxidising agents.
10.4 Conditions to avoid Conditions to avoid	:	Extremes of temperature and direct sunlight.
10.5 Incompatible materials		
Materials to avoid	:	Strong oxidising agents.
10.6 Hazardous decomposition pr	oc	lucts
Hazardous decomposition	:	No decomposition if stored and applied as directed.

products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	:	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		

Product:

Acute oral toxicity	LD50 rat: > 5,000 mg/kg
	Remarks: Low toxicity:
	Based on available data, the classification criteria are not met.

AeroSheli Fiulu Si		
Version 4.7	Revision Date 26.03.2021	Print Date 27.03.2021
	Remarks: Aspiration into the lungs pneumonitis which can be fatal.	may cause chemical
Acute inhalation toxicity	: Remarks: Based on available data, are not met.	the classification criteria
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classi	fication criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: For respiratory and skin sensitisation:, Not a sensitiser., Based on available data, the classification criteria are not met.

Components:

Triazole derivative:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
----------	--

Vers	sion 4.7	Revision Date 26.03.2021	Print Date 27.03.2021
	Alkylphenol	No carcinogenicity classification.	
	Triphenyl phosphate	No carcinogenicity classification.	

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Version 4.7

sion 4.7	Revision Date 26.03.2021	Print Date 27.03.2021

•	y on evaluation of the CMR properties	
Germ cell mutagenicity- Assessment	: This product does not meet the criteria for classification in categories 1A/1B.	
Carcinogenicity - Assessment	: This product does not meet the criteria for classification in categories 1A/1B.	
Reproductive toxicity - Assessment	: This product does not meet the criteria for classification in categories 1A/1B.	

SECTION 12: Ecological information

12.1 Toxicity

Basis for assessment	:	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Toxicity to fish (Acute toxicity)	:	Remarks: LL/EL/IL50 >10 <= 100 mg/l Harmful
Toxicity to crustacean (Acute toxicity)	:	Remarks: LL/EL/IL50 >10 <= 100 mg/l Harmful
Toxicity to algae/aquatic plants (Acute toxicity)	:	Remarks: LL/EL/IL50 >10 <= 100 mg/l Harmful
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available
Toxicity to crustacean (Chronic toxicity)	:	Remarks: Data not available
Toxicity to microorganisms (Acute toxicity)	:	Remarks: Data not available

<u>Components:</u> Phenol, isobutylenated, phosphate (3:1) :

M-Factor (Short-term (acute) : 1

Version 4.7 Revision Date 26.03.2021 Print Date 27.03.2021 aquatic hazard) Triazole derivative : M-Factor (Short-term (acute) : 1 aquatic hazard) M-Factor (Long-term : 1 (chronic) aquatic hazard) 12.2 Persistence and degradability Product: Biodegradability : Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment. 12.3 Bioaccumulative potential **Product:** Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate. Partition coefficient: n-: log Pow: > 6Remarks: (based on information on similar octanol/water products) 12.4 Mobility in soil **Product:** Mobility : Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile. Remarks: Floats on water. 12.5 Results of PBT and vPvB assessment **Product:** Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB. 12.6 Other adverse effects Product: Additional ecological : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product information is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use. Poorly soluble mixture., Causes physical fouling of aquatic organisms.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Fluid 31

Version 4.7	Revision Date 26.03.2021	Print Date 27.03.2021
Product	: Recover or recycle if possible. It is the responsibility of the waste of toxicity and physical properties of the determine the proper waste classifi methods in compliance with applicat Do not dispose into the environmer courses	ne material generated to cation and disposal able regulations.
	Waste product should not be allow ground water, or be disposed of int Waste, spills or used product is dar Waste arising from a spillage or tar disposed of in accordance with pre preferably to a recognised collector competence of the collector or cont established beforehand. Do not dispose of tank water bottor drain into the ground. This will resu contamination.	o the environment. ngerous waste. ik cleaning should be vailing regulations, or contractor. The tractor should be ms by allowing them to
	MARPOL - see International Conve Pollution from Ships (MARPOL 73/ technical aspects at controlling poll	78) which provides
Contaminated packaging	: Dispose in accordance with prevail to a recognized collector or contract the collector or contractor should be Disposal should be in accordance national, and local laws and regular	tor. The competence of e established beforehand. with applicable regional,
Local legislation		
Waste catalogue		
	EU Waste Disposal Code (EWC):	
Waste Code	: 13 01 11*	
Remarks	: Disposal should be in accordance with a store in accordance with a store in attempts and regular store in a	
	Classification of waste is always the user.	e responsibility of the end
	Hazardous Waste (England and W	ales) Regulations 2005.

Version 4.7

Revision Date 26.03.2021

Print Date 27.03.2021

SECTION 14: Transport information

14.1 UN number		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 Proper shipping name		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.5 Environmental hazards		
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
14.6 Special precautions for user		
Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)

: Product is not subject to Authorisation under REACH.

Volatile organic compounds : 0 %

ersion 4.7	Revision Date 26.03.2021	Print Date 27.03.20			
Other regulations		The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.			
	Environmental Protection Act 1990 (Safety at Work etc. Act 1974. Consu- Pollution Prevention and Control Ac 1995. Factories Act 1961. The Carri and Use of Transportable Pressure Regulations 2011. Chemicals (Haza Packaging for Supply) Regulations 2 Substances Hazardous to Health Re amended). Merchant Shipping (Dan Pollutants) Regulations 1997. Repor and Dangerous Occurrences Regula Personal Protective Equipment Reg Protective Equipment at Work Regula Control of Major Accident Hazards F amended). Renewable Transport Fu (as amended). Energy Act 2011. En (England and Wales) Regulations 2 (England and Wales) Regulations 2 Planning (Hazardous Substances) A regulations. The Environmental Prot Ozone-Depleting Substances) Regula	umers Protection Act 1987. t 1999. Environment Act age of Dangerous Goods Equipment (Amendment) Ind Information and 2009. Control of egulations 2002 (as gerous Goods and Marine rting of Injuries, Diseases ations 1995 (as amended). ulations 2002. Personal lations 1992. Hazardous tions 2005(as amended). Regulations 1999 (as uel Obligations Order 2007 vironmental Permitting 010 (as amended). Waste 011 (as amended). Act 1990 and associated rection (Controls on			
	Regulation (EC) No 1907/2006 of th and of the Council of 18 December 2 Registration, Evaluation, Authorisati Chemicals (REACH), annex XIV. Regulation (EC) No 1907/2006 of th and of the Council of 18 December 2 Registration, Evaluation, Authorisati Chemicals (REACH), annex XVII. Directive 2004/37/EC on the protect risks related to exposure to carcinog and its amendments. Directive 1994/33/EC on the protect work and its amendments. Council Directive 92/85/EEC on the to encourage improvements in the s pregnant workers and workers who or are breastfeeding and its amendments	2006 concerning the on and Restriction of e European Parliament 2006 concerning the on and Restriction of ion of workers from the gens or mutagens at work ion of young people at introduction of measures afety and health at work of have recently given birth			

The components of this product are reported in the following inventories:

REACH	:	All components listed or polymer exempt.
TSCA	:	Notified with Restrictions.

15.2 Chemical safety assessment

Version 4.7

Revision Date 26.03.2021

Print Date 27.03.2021

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

REGULATION (EC) No 1272/2008	Classification procedure:
Aspiration hazard, Category 1, H304	Expert judgement and weight of evidence
	determination.
Long-term (chronic) aquatic hazard,	Expert judgement and weight of evidence
Category 3, H412	determination.

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute Aquatic Chronic Asp. Tox. Skin Corr. Skin Sens. Abbreviations and Acror	Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Aspiration hazard Skin corrosion Skin sensitisation yms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
	ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals ECHA = European Inventory of Existing Commercial Chemical Substances

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

AeroShell Fluid 31	Povision Date 26.02.2021	Drint Data 07.02.000
/ersion 4.7	Revision Date 26.03.2021	Print Date 27.03.202
	EL50 = Effective Loading fifty ENCS = Japanese Existing and New Inventory EWC = European Waste Code GHS = Globally Harmonised System Labelling of Chemicals IARC = International Agency for Res IATA = International Air Transport A IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG = International Maritime Dang INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test determination of polycyclic aromatic KECI = Korea Existing Chemicals In LC50 = Lethal Concentration fifty LD50 = Lethal Loading/Effective LL50 = Lethal Loading fifty MARPOL = International Convention Pollution From Ships NOEC/NOEL = No Observed Effect Observed Effect Level OE_HPV = Occupational Exposure PBT = Persistent, Bioaccumulative a PICCS = Philippine Inventory of Che Substances PNEC = Predicted No Effect Conce REACH = Registration Evaluation A Chemicals RID = Regulations Relating to Interr Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Cont TWA = Time-Weighted Average vPvB = very Persistent and very Bic	m of Classification and search on Cancer Association gerous Goods (method N° 346 for the cs DMSO-extractables inventory Loading/Inhibitory loading in for the Prevention of t Concentration / No - High Production Volume and Toxic emicals and Chemical entration And Authorisation Of national Carriage of
Further information		
Training advice	: Provide adequate information, instru operators.	uction and training for
Other information	: A vertical bar () in the left margin in from the previous version.	idicates an amendment
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but not lin sources of information (e.g. toxicolo Health Services, material suppliers' IUCLID date base, EC 1272 regulat	ogical data from Shell data, CONCAWE, EU

Version 4.7

Revision Date 26.03.2021

Print Date 27.03.2021

Identified Uses according Uses - Worker	to t	he Use Descriptor System
Title	:	General use of lubricants and greases in vehicles or machinery Industrial
Uses - Worker Title	:	General use of lubricants and greases in vehicles or machinery Professional

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Version 4.7

Revision Date 26.03.2021

Exposure Scenario - Worker	
30000010677	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 8b, PROC 9 Environmental Release Categories: ERC4, ERC7, ATIEL- ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

Section 2.1	Control of Worker Exposure
Product Characteristics	

Contributing Scenarios	Risk Management Measures
eenting eeenanee	i iii iii anageinent measares

Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per yea	ar):	2,631.1
Fraction of EU tonnage use	d in region:	0.1
Fraction of Regional tonnag	je used locally:	0.1
Frequency and Duration of	of Use	
Emission Days (days/year):		300
Environmental factors no	t influenced by risk management	
Local freshwater dilution fac	ctor:	10
Local marine water dilution	factor:	100
Other Operational Conditions affecting Environmental Exposure		
Negligible wastewater emis	sions as process operates without water	
contact.		
Release fraction to air from process (after typical onsite RMMs) :		5.00E-05
Release fraction to wastewater from process (after typical onsite		2.00E-11
RMMs and before (municipal) sewage treatment plant):		
Release fraction to soil from process (after typical onsite RMMs):		0
Technical conditions and	measures at process level (source) to p	prevent release
Common practices vary acr	oss sites thus conservative process	
release estimates used.		
	ns and measures to reduce or limit disc	harges, air
emissions and releases to		
Treat air emission to provid	e a typical removal efficiency of (%)	70

Print	Date	27	ია	2021	
гшц	Dale	Z1.	US.	.2021	

Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
User sites are assumed to be provided with oil/water separators or	
equivalent and for waste water to be discharged via public sewer	
system.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	olant
Estimated substance removal from wastewater via domestic sewage	87.3
treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2.00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs	392,538.9
as above (kg/day) :	
Conditions and Measures related to external treatment of waste fo	r disposal
External treatment and disposal of waste should comply with applicable	e local and/or regional
regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable	local and/or regional
regulations.	
5	

Revision Date 26.03.2021

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 - Environment

Version 4.7

Used ECETOC TRA model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE
	EXPOSURE SCENARIO

Section 4.1 - Health

No exposure assessment presented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.

Version 4.7

Revision Date 26.03.2021

Exposure Scenario - Wo 300000010678	orker
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 8a, PROC 8b, PROC 20 Environmental Release Categories: ERC9a, ERC9b, ESVOC SpERC 9.6b.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

Section 2.1	Control of Worker Exposure
Product Characteristics	

Contributing Scenarios Risk Management Measures

Section 2.2	Control of Environmental Exposure	e	
Amounts Used			
EU tonnage (tonnes per year):		5,387.2	
Fraction of EU tonnage used in region:		0.1	
Fraction of Regional tonnage used locally:		0.1	
Frequency and Duration of	Use		
Emission Days (days/year):		365	
Environmental factors not	nfluenced by risk management		
Local freshwater dilution factor:		10	
Local marine water dilution factor:		100	
Other Operational Conditio	ns affecting Environmental Exposur	e	
Negligible wastewater emissions as process operates without water			
contact.			
Release fraction to air from process (after typical onsite RMMs) :			
Release fraction to wastewater from process (after typical onsite		5.00E-04	
RMMs and before (municipal) sewage treatment plant):			
Release fraction to soil from process (after typical onsite RMMs):		1E-03	
Technical conditions and n	neasures at process level (source) to	prevent release	
	ss sites thus conservative process		
release estimates used.			
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil			

Version 4.7

Revision Date 26.03.2021

Print Date 27.03.2021

Prevent discharge of undissolved substance to or recover from onsite		
wastewater.		
Organisational measures to prevent/limit release from site		
Do not apply industrial sludge to natural soils.		
Sludge should be incinerated, contained or reclaimed.		
Conditions and Measures related to municipal sewage treatment plant		
Estimated substance removal from wastewater via domestic sewage	87.3	
treatment (%)		
Assumed domestic sewage treatment plant flow (m3/d)	2.00E+03	
Maximum allowable site quantity (MSafe) based on OCs and RMMs	3,821.4	
as above (kg/day) :		
Conditions and Measures related to external treatment of waste fo	r disposal	
External treatment and disposal of waste should comply with applicable local and/or regional		
regulations.		
Conditions and measures related to external recovery of waste		
External recovery and recycling of waste should comply with applicable local and/or regional		
regulations.		

SECTION 3	EXPOSURE ESTIMATION	
Section 3.1 - Health		
No exposure assessment presented for human health.		

Section 3.2 - Environment

Used ECETOC TRA model.

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

No exposure assessment presented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.